

COBRA 45/60 Range

Floor Saws

The **COBRA** series machines are rough and all-round, with an excellent output.

Both of them include a polypropylene water tank of 40 or 50 litres depending on the model (10.5 gal. or 13.2 gal.).

Though very robust, the design is ergonomic to provide an easy use and to ensure unbeatable performance in large areas such as motorways, roads, industrial buildings, airports, etc.

Great performance and versatility.

- Depth indicator.
- Two ways blade cooling system, either from the built-in water tank or the water mains.
- Push feed (**COBRA 45**) or mechanical hand wheel operated (**COBRA 60**).
- Cutting adjustment by handle with locking system.
- Cutting depth control by trapezoidal thread shaft on a cast iron housing mounted gear.
- Especially designed for heavy duty, including rental works.
- Easy access to the blade.



COBRA 45 HONDA

FEATURES AND BENEFITS OF THE COBRA RANGE



Rubber band wheels with ball bearings.



Cutting depth operated by trapezoidal thread shaft.



Trapezoidal transmission belts (Honda and Lombardini).




Poly-V belt transmission (Yanmar).



Water cooling fork, reaching both blade sides.



40 or 50 litres water tank (model **COBRA 40** or **COBRA 50** respectively).



Robust chassis.




Cutting depth indicator.

HOW TO CUT:



1

Two parallel guiding lines must be **drawn** on the surface to cut.



2

We proceed to **cut** the first line, and then we cut the second on return.



3

The excavator can then start to dig.



COBRA 60 LOMBARDINI

COBRA 45 YANMAR

Multiple Cut



The **COBRA Vario** concept regards the possibility of producing multiple parallel cuts by using more than one blade (see page 69).

	COBRA 45		
Item code	2565	2603*	2585
Motor type	4-stroke / Diesel		
Model motor	Yanmar L100AE - DYC	Honda GX390	Honda GX390 CYC
Motor starter	Recoil		
HP	10	13	
Blade bore diameter (mm / in)	25,4 / 1"		
Max. blade diameter (mm - in)	450 / 500 - 18" / 20"		
Max. cutting depth (mm - (in)	145 / 170 - 5,7" / 6,7"	145 / 170 - 5,7" / 6,7"	145 / 170 - 5,7" / 6,7"
Water tank capacity (L. Gal.)	40 / 10,5		
Net weight (Kg. / lbs.)	125,5 / 276,6	110 / 242,5	
Packaging dimensions L x W x H (mm / in)	1180 x 670 x 1050 / 46,4" x 26,3" x 41,3"		
Disc included	No		

*No CE

	COBRA 60			
Item code	2506	2507	2508	2509
Motor type	Gasoline 4 T			
Model motor	Honda GX390	Honda GX390 CYC	Honda GX630	Lombardini MD 190
Motor starter	Recoil		Electric	
HP	13		23	16
Blade bore diameter (mm / in)	25,4 / 1"			
Max. blade diameter (mm / in)	600 / 24"			
Max. cutting depth (mm / (in)	200 / 7,8"			
Water tank capacity (L. Gal.)	50 / 13,2			
Net weight (Kg. / lbs.)	188 / 414	234 / 516		245 / 540
Packaging dimensions L x W x H (mm / in)	1480 x 830 x 1190 / 58,2" x 32,6" x 46,8"			
Disc included	No			