

# DRILL 9

## Core Drill Motor

- Three-position speed selector.
- Anti-shock electric safety system (PRCD wire)
- Mechanical friction clutch to release the motor in case of jammed core bit.
- Heat treated cogwheels for improved resistance.
- Connecting thread 1 1/4" UNC.
- Aluminium body and water inlet included.



	<b>DRILL 9</b>
	<b>1 - PHASE</b>
Item code	9320
Motor voltage (V)	230
Frequency (Hz / Plug)	50 / 60
Kw	3,5
Max. drilling diameter (mm / in)	452 / 18"
R.P.M. 1 <sup>st</sup> speed / 2 <sup>nd</sup> speed / 3 <sup>rd</sup> speed	300 / 600 / 900
Net weight (Kg. / lbs.)	13 / 28,6
Packaging dimensions (L x W x H (nm / in)	570 x 200 x 200 / 22,4" x 7,8" x 7,8"

# RIG

## Drill columns

- Two strong rig models available, both made of anodized aluminium with a tube core and featured with 2 rack tracks.
- 40 x 40 x 3 mm in **RIG 3** (1.6" x 1.6" x 0.11").
- 50 x 50 x 3 mm in **RIG 5** (1.6" x 1.6" x 0.11").
- Self adjusting wheels.
- Featured with a drill bit centering device.
- Tipping safe system in the base and the wheels.
- Prepared to use vacuum pump (only RIG 3).



	<b>RIG 3</b>	<b>RIG 5</b>
Item code	9340	9350
Max. drilling diameter (mm / in)	352 / 13,8"	452 / 18"
Speed reducer gearbox	No	Yes
Net weight (Kg. / lbs.)	22 / 48,5	24,6 / 54,2
Packaging dimensions (L x W x H (nm / in)	1110 x 330 x 450 / 43,7" x 13" x 17,7"	1110 x 380 x 450 / 43,7" x 15" x 17,7"

### FEATURES AND BENEFITS OF THE RIG RANGE

