

ACCESSORIES

OUTPUT

CUTTING DEPTH

R-0733194
WATERPROOF BEARINGS
SEALED UCFL 205
 WITH RUBBER SEAL AND O-RING
 PRESSURE WASHER PROOF



R-0325177
HOUR / RPM COUNTER
WATERPROOF - IP 68
 PROGRAMMABLE WITH 3 MAINTENANCE ALERTS:
 AIR FILTER, OIL REPLACEMENT, CUSTOM ALERT.



R152018009901
EASY & FAST BELT TENSIONER

BELTS REPLACEMENT AND
 TENSIONING IN 5 MIN.
 NO ENGINE MOVE OR PULL
 ALIGNMENT REQUIRED.



3 BLADES 15 MM
RUNS 45 CM / MIN.

1 BLADES 3 MM
RUNS 1 M / MIN.

| BLADE | DEPTH | M/S |
|-----------------|-------|-----|
| Ø500MM / 185 CM | | 69 |
| Ø450MM / 160 CM | | 62 |
| Ø400MM / 135 CM | | 55 |
| Ø350MM / 110 CM | | 48 |
| Ø300MM / 85 CM | | 41 |



| | | |
|-----------------------|---------------------------------------|------------------|
| Engine | Honda GX 390 CYC | Kohler CH440 CYC |
| Fuel | Gasoline | |
| Starter | Recoil | |
| Power | 9,6 Kw / 13HP | 10,3 Kw / 14HP |
| Feed | Manual | |
| Ø Max blade | Ø 500 mm | |
| Ø Bore | Ø 25,4 mm | |
| Blade location | Right side | |
| Water deposit | 40 L / 10.5 Gal | |
| Blade cooling | 2 blade sides | |
| Nett weight | 89 Kg / 196 Lb | |
| Cutting depth control | Heavy-duty gas shock absorber | |
| Dimensions LxAxH | 1529" x 656" x 915" / 60" x 26" x 36" | |



COBRA 45 PRO



MULTI-BLADE FLOOR SAW

ALL IN ONE

Ø300 - Ø350 - Ø400 - Ø450 - Ø500



SPECIAL KIT:
MICRO-TRENCHING AND JOINTS CUTTING

R152018009900
TRENCH 15MM WITH NO CENTER
3 BLADES Ø400 MM CONCRETE
2 SPACERS 2.5 MM



Pol. Juncaril, C/Albuñol, Parc. 250
 18220 Albolote, Granada, Spain
 Telf. +34 958 490 410
 Fax: 34 958 466 645