


**MAGNUM Range** 



## FEATURES AND BENEFITS OF THE MAGNUM RANGE




litres (10.5 gal.) per minute.

and to afford extra heavy materials.

3. The bed frame is reinforced to make it more robust








MADE IN SPI

o sima









## **Great cutting capacity.**

- Handwheel operated mechanical feed, allowing a smooth effortless scrolling.
- Easy regulation of the cutting height with a very effective and safe locking system.
- Lasting durability, as it is built on a rugged monobloc chassis, and easy to move, as it is featured with four lockable wheels.
- Transmission by belts, providing a smooth and quiet operation and a high cutting accuracy.
- The diamond blade is cooled with water pumped from the tub or directly from the water mains.
- Large galvanized steel water tub, able to hold up to 87 litres (50 gal.), removable for easy cleaning.
- Long-life sealed bearings specially designed to work in a wet working environment.
- All the electronic parts comply with the different applicable European norms and regulations.
- Maximum cutting length up to 844 mm (33.2").
- Maximum cutting depth up to 420 mm (16.5").



For cutting a wide variety of materials											
							9				7
	Materials	Bricks	Slate	Terrazzo	Concrete	Poroton	Ytona	Sandstone	Kerbstone	Granite	Marble

	MAGNUM 700	MAGNUM 1000			
	3 - PHASE	3 - PHASE			
Item code	6551	6552			
Motor voltage (V)	400	400			
Frequency (Hz) / In (pins)	50/5P	50/5P			
Kw (Hp)	5,5 (7,5)	7,5 (10)			
Water tub capacity (L. / Gal.)	87 / 22,9	87 / 22,9			
Blade diameter (mm / in)	725 / 28"	1000 / 40"			
Blade bore diameter (mm / in)	60 / 2,3"	60 / 2,3"			
Blade included (mm / in)	No	No			
Max. cutting length (mm / in)	844/33,2"	702 / 27,6"			
Max. cutting depth (mm / in)	272 / 10,7"	420 / 16,5"			
Net weight (Kg. / lbs.)	280 / 617,2	303/668			
Packaging dimensions L x W x H (mm/in)	2160 x 1260 x 1500 / 85" X 49,6" x 59"	2160 x 1260 x 1500 / 85" X 49,6" x 59"			